



Heat recovery ventilation units
& accessoires

GROUP



High efficient counterflow heat exchanger



NEW:
Made in Belgium by Sanutal

TALiN
340 - 480

Type of unit	TALLiN 340	TALLiN 480
Ventilator type	EBM-Papst type EC	EBM-Papst type EC
Mains voltage	230 VAC	230 VAC
Frequention	50 Hz	50 Hz
Control possibilities	RF-4 operation modes /built-in clock logic Tablet Controllable	RF-4 operation modes /built-in clock logic Tablet Controllable
Type of ventilation control	Constant Flow	Constant Flow
Thermal efficiency heat exchanger	+ 90%	+ 90%
Material heat exchanger	Synthetic	Synthetic
CE approval	Yes	Yes
Certificats	Yes	Yes - in demand
Filtration	EU3	EU3
Bypass automatic	Yes	Yes
Max flow	340 m ³ /h (94.5 l/s) by 150Pa	480 m ³ /h (133 l/s) by 150Pa
Max power	171 Watt	340 Watt
Ethernet	Yes	Yes
SD Card	Yes	Yes
RS485	Yes	Yes
USB	Yes	Yes
External connectivity	Emergency Contact, CO ₂ - sensor, humidity sensor, temperature sensor, pressure sensor, PIR - sensor <i>not all combinations are possible</i>	Emergency Contact, CO ₂ - sensor, humidity sensor, temperature sensor, pressure sensor, PIR - sensor <i>not all combinations are possible</i>
Digital control panel	Option	Option
Installation possibilities	Ceiling and wall	Ceiling and wall
Housing dimensions EPP	715 x 1150 x 295 mm	715 x 1150 x 295 mm
Weight unit	18 kg	18 kg
	99.tallinn340	99.tallinn480

GROUP

K

High efficient counterflow heat exchanger



NEW:
Made in Belgium by Sanutal

TALLiN

600-1000-2000

Ventilator type	TALLiN 600	TALLiN 1000	TALLiN 2000
Mains voltage	Ziehl Abegg type EC	Ziehl Abegg type EC	Ziehl Abegg type EC
Frequention	230 VAC	230 VAC	230 VAC
Control possibilities	50 Hz	50 Hz	50 Hz
Type of ventilation control	RF-4 operation modes /built-in clock logic Tablet Controllable	RF-4 operation modes /built-in clock logic Tablet Controllable	RF-4 operation modes /built-in clock logic Tablet Controllable
Thermal efficiency heat exchanger	Constant Flow	Constant Flow	Constant Flow
Material heat exchanger	+ 90%	+ 90%	+ 90%
CE approval	Aluminium	Aluminium	Aluminium
Certificats	Jes	Jes	Jes
Filtration	on demand	on demand	on demand
Bypass automatic	G4	G4	G4
Max flow	Yes	Yes	Yes
Max power	600 m ³ /h bij 150Pa	1000 m ³ /h bij 150Pa	2000 m ³ /h bij 150Pa
Ethernet	420 Watt	1000 Watt	1000 Watt
SD Card	Yes	Yes	Yes
RS485	Yes	Yes	Yes
USB	Yes	Yes	Yes
External connectivity	Yes	Yes	Yes
Digital control panel	Emergency Contact, CO ₂ - sensor, humidity sensor, temperature sensor, pressure sensor, PIR - sensor <i>not all combinations are possible</i>	Emergency Contact, CO ₂ - sensor, humidity sensor, temperature sensor, pressure sensor, PIR - sensor <i>not all combinations are possible</i>	Emergency Contact, CO ₂ - sensor, humidity sensor, temperature sensor, pressure sensor, PIR - sensor <i>not all combinations are possible</i>
Installation possibilities	Option	Option	Option
Housing dimensions EPP	Ceiling	Ceiling	Ceiling
Dim unit	900 x 1700 x 370 mm	1100 x 1750 x 450 mm	1530 x 2000 x 500 mm
Gewicht toestel	on demand	on demand	on demand
Art. number	99.tallinn600	99.tallinn1000	99.tallinn2000

Accessories

Connection Kit Tallinn 340 - 480



Description	Art. number
connection Kit Ø 180 mm with clips 4 pieces	99.AANSLUITPAKKET



RF transmitter

Description	Art. number
RF transmitter 4 positions	99.TALRFZENDER



Combi grill

Description	Art. number
Combi grill 2x Ø 180 mm	99.TALCOMBIROOSTER